

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒
well well other

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
501 Airport Drive, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 790' FNL x 1055' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Spud & Set Casing		

5. LEASE
Jicarilla Apache 102

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jicarilla Apache 102

9. WELL NO.
7E

10. FIELD OR WILDCAT NAME
B. S. Mesa Gallup/Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
NW/4, NW/4, Section 3, T26N, R4W


12. COUNTY OR PARISH
Rio Arriba

13. STATE
NM

14. API NO.
30-039-22453

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7170' GL

(NOTE: Report results of multiple completion operations change on Form 9-330)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 13-1/2" hole on 8-17-80 and drilled to 322'. Set 9-5/8", 32.3# surface casing at 322' on 8-18-80 and cemented with 315 sx of class "B" Neat cement containing 2% CaCl₂. Good cement was circulated to the surface. Drilled a 8-3/4" hole to a depth of 4250'. Set 7", 23.0# intermediate casing on 8-25-80 at 4250' and cemented with 720 sx of class "B" cement containing 50:50 Poz, 6% gel, 2# Medium tuf plug per sx, and .8% fluid loss additive. This was tailed in with 100 sx of class "B" Neat cement. No cement was circulated to the surface. Drilled a 6-1/4" hole to a TD of 8407'. Set 4-1/2" production casing at 8407' on 9-2-80 and cemented with 475 sx of class "B" cement containing 50:50 Poz, 6% gel, 2# Medium tuf plug per sx, and .8% fluid loss additive. This was tailed in with 200 sx of class "B" Neat cement. No cement was circulated to the surface. The rig was released on 9-2-80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

Original Signed By
SIGNED E. E. SYOBODA TITLE Dist. Adm. Supvr. DATE 9-12-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

SEP 22 1980

BY SW FARMINGTON DISTRICT

*See Instructions on Reverse Side

NMOCC