## UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	Jicarilla Contract 155
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1 oil gas	Jicarilla Contract 155
1. oil gas well other	9. WELL NO. 31
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME
Amoco Production Company 3. ADDRESS OF OPERATOR	Otero Chacra/South Blanco P.C.
501 Airport Dr., Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA SE/4, NE/4, Section 29, T26N, R5W
AT SURFACE: 1620' FNL x 880' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	Rio Arriba NM
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	30-039-22569
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6459 GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT USE SHOOT OR ACIDIZE USE USE USE USE USE USE USE USE USE US	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9–330.)
MULTIPLE COMPLETE	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
ABANDON*	
(other) Completion	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is demeasured and true vertical depths for all markers and zones pertiner Completion operations commenced 7-28-82. Total	irectionally drilled, give subsurface locations and it to this work.)* al depth of the well is 3982, and
plugback depth is 3933'. Perforated Chacra i	ntervals 3824-3792', 3742-3710',
with 2 spf, a total of 128 .40" holes. Frac	with 89,000 gallons of 70%
quality foam and 162,000 lbs. 10-20 sand. Per 2874-2836' with 2 spf, a total of 76, .40" ho	errorated Pictured Uliffs interval
70% quality foam and 51,335 lbs. 10-20 sand.	Landed 2-1/16" Chacra tuhing
at 3826' and 1-1/4" PC tubing at 2894'. Rel	Leased rig on 8-17-82.
7	
in the second of	
Subsurface Safety Valve: Manu. and Type	Set @Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED TITLE Admin. Supvi	9-1-82
(This space for Federal or State of	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE
	ALUM PTER MOR DECORD

\*See Instructions on Reverse Side