STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	New Mexico N	ORTHWEST NE				Well or	
	Tenneco Oil Co.			Jicarilla		_ No	
rator tion J	. 16 T	26N	Rgc	5W	County	, <u>Rio Arriba</u>	
ell: Unit Sec Twp 26N		TYPE OF PRO	00.	METHOD OF PROD. (Flow or Art. LHt)	PROD. MEDIUM (Tbg. or Csg.)		
er Chaon	Character			shut in		tubing	
	Davis Dakata			flow		tubing	
etion Basin	Dakota	PRF.FI O	W SHUT-IN PR	ESSURE DAT	Α		
		Length of time shut-		Si press. psig	S	Stabilized? (Yes or No)	
Hour date		72 h	rs	880		Ves Stabilized? (Yes or No)	
:Hour, date	:Hour, date shul-in Length of time st		•111	Si press. pelg 1240	ľ	yes	
pletion 2:30	7/19/87	72 h	irs.	1240			
			FLOW TEST	NO. 1			
of Chourt	ate)* 2:30 7	//22/87		Zone producing	(Upper or Lower):	lower	
AND THE		PRES		PROD. ZONE TEMP.	ſ	REMARKS	
TIME (hour, date)	SINCE*	Upper Completion	Lower Completion	1			
2:30 7/23/87	24 hrs	880	900				
2:30 7/24/87	48 hrs	880	560				_
		;			- 13 5 to	EIVED	
					AUG	0.3100=	
		.*			OIL CO	O MISS ES	
					Dis	0 71987 DIV.	
aduction tate	during test						
oduction rate	during test		Rhle	in H			
oduction rate	during test	PD based on	Bbls.	in H	ours(GravGOR	
ü:	BO	мс	FPD; Tested th	ru (Orifice or I	ours(GravGOR	
il:	BO	мс	FPD; Tested th	nu (Orifice or I	ours(GravGOR	
il: as:	BO	мс	FPD; Tested th	ru (Orifice or I	ours(GravGOR	

FLOW TEST NO. 2

mmenced at (hour, date) 本本				Zone producing (Upper or Lower):		
TIME	LAPSED TIME	PRESSURE				
(hour, date)	SINCE ##	Upper Completion	Lower Completion	PROD. ZONE TEMP.	REMARKS	
					-	
uction rate d	uring test					
	_				- ·	
	BOPE	based on	Bbls. in	Hours.	Grav GOR	
		MCE	3D 7 1 1		GOR	
		— MCFF	D: lested thru (Orifice or Meter):		
uks:					·	
		····				
eby centify th	at the information	n herein containe	d is true and con	Oblete to the hear	of my knowledge.	
oved	AUG n	7 1007		T.	or my knowledge.	
w Mexico Oil	Conservation Di	vision	- 19 O _I	perator	of my knowledge.	
			1 0		ohn Carter to his august	
	Original Signed by	CHARLES GHOLSO	N		7.	
,			Ti1	leAg	lent	
DEPUTY OIL & GAS INSPECTOR, DIST. #3				** 7/	28/87	
		7	D2	ıc//	<u> </u>	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Ten No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such ten shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage ten, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Ten No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is so be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shur-in while the zone which was previously shur-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at housity intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least rwice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packet Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).