

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 870' FWL, 1850' FNL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:


☐
☒
☐
☐
☐
☐
☐
☐
☐

RECEIVED

AUG 13 1982

U.S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

(NOTE: Report results of multiple completion or zone change on Form 9-330)



5. LEASE

Contract #109

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla B

9. WELL NO.

5E

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21, T26N, R5W

12. COUNTY OR PARISH

Rio Arriba, NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6578' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/28/82 - MIRUSU. NDWH. NDBOP. Tallied and RIH w/tbg. Bit sub and 3-7/8" bit. Tagged cmt. @ 2640'. 120' above DV tool @ 2583'. Drill cmt and DV tool. RIH to 3928'. Drld to 4018'.
7/29/82 - Drl DV @ 4018'. RIH w/tbg. to 7340'. Tagged cmt. Drld. cmt. to FC @ 7456'. PT csg to 3500 psi. OK. Circ. hole w/1% KCL wtr. Spot 500 gals. of 7½% HI HCL @ 7420'. POOH w/tbg; bit sub and bit. RIH w/GR and CCL. Run cmt. bond log from PBTD of 4000'. Perf'd. B&D zone in Dakota w/1 JSPF using 3-1/8" csg. gun, 7319-35', 7366-84', 7405-18'; 47', 47' holes

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Renise Wilson TITLE Production Analyst DATE August 3, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 17 1982

*See Instructions on Reverse Side

NMOC

BY

FARMINGTON DISTRICT