

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Curtis J. Little

3. ADDRESS OF OPERATOR
P. O. Box 2487
Farmington NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1800'FNL & 1840'FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)
OCT 07 1982

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
SF-080136

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
SALAZAR

9. WELL NO. #6

10. FIELD OR WILDCAT NAME
Ballard PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 34-T25N-R6W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
N.M.

14. API NO. 30-039-23060

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6365'GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 10-3-82 SPUD 3:00pm 10-2-82. Drld 115'GR of 9-7/8" hole & ran 112'GR 7" 23# csg. Cemented w/65 sx w/2% CaCl & 1/4# Floseal (77cf). Good circulation of cement to surface. Plug down 5:00 pm. WOC 12 hrs. Pressure tested 600 psi. Held OK. Dev. 0°@ 115'. Drlg. w/bit #2. Mud wt 8.6#, vis 30, WL 12.
- 10-5-82 TD at 6:00 pm 10-5-82. Ran 72 jts 2-7/8" 6.5# J-55 csg to 2325'GR. PBTD 2312'GR. Howco cemented w/350 sx 50-50 pos 6% gel & 6 1/4# gilsonite & 50 sx Class B Neat. Total slurry 690cf. Circulated 75 cf cement to pits. Pressured up to 3500 psi. Held OK. Plug down 3:45 pm 10-6-82.

Subsurface Safety Valve: Manu. and Type n/a Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Curtis J. Little TITLE Operator DATE 10-7-82

(This space for Federal or State office use)

APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

OCT 03 1982

NMOCC

FARMINGTON, N.M.
BY Sm m