

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well well
2. NAME OF OPERATOR
Tenneco Oil Company
3. ADDRESS OF OPERATOR
P.O. Box 3249, Englewood, CO 80155
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 950' FNL, 1765' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
AUG 1 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
AUG 8 - 1983

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

CON. DIV.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/2/83: Spud @ 12:01 am 7/2/83 w/ 4 corners rig #7. Run 7 jts 9 5/8" 36# K-55 ST&C csg (283') set @ 298' cmt w/ (354 CF) CL-B + 2% CaCl₂ + 1/4#/sx D-29, PD @ 5:45 pm 7/2/83. Circ cmt to surface. Pt stack, csg etc to 1000 psi, OK.

7/9/83: Reach INTD csg PT 6 pm 7/9/83.

7/10/83: Run 83 jts 7" 23# N-80 LT&C & 46 jts 7" 23# K-55 LT&C csg (5559') set @ 5550, FC @ 5493 & DV @ 2943. cmt 1st stage w/ 412 sx (486 CF) c1-B + 2% CaCl₂, PD @ 5:30 pm 7/10/83. No cmt circ. cmt 2nd stage w/ 331 sx (563 CF) 65:35 POZ + 6% gel + 1/4#/sx Flocele + .4% perlite + 2% CaCl₂. PD @ 8:30 pm 7/10/83. circ to surface.

7/16/83: TD 7498', RU & run 47 jts 4 1/2 11.6# N-80 LT&C csg, 2111', set @ 7498', tol @ 5376 LC @ 7451.

7/17/83: cmt w/ 150 sx (276CF) 65:35 POZ + 6% gel + 1/4#/sx D-29, tail by 150 (over)

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Analyst

DATE

ACCEPTED FOR RECORD
7/28/83

Original Signed by FRANK T. CHAVEZ

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

AUG 8 - 1983
AUG 0 4 1983

FARMINGTON RESOURCE AREA
FARMINGTON, NEW MEXICO

BY

7/8

*See Instructions on Reverse Side

NMOCC

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-166

7/17/83: (con't) sx (177CF) C1-B + 1/4#/sx D-29. PD @ 7:30 7/17/83.