

5 BLM 1 Celsius-SLC 1 Celsius-Denver
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved. 1 File
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

OCT 16 1986

1. Mancos Dakota

OIL WELL ☒ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR

P O Box 208, Farmington, NM 87499

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1780' FSL & 2120' FWL

5. LEASE DESIGNATION AND SERIAL NO.

NM 28709

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Divide

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Gavilan Mancos/
Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 35, T26N, R2W, NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, ET, GR, etc.)

7695' GL

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud, surface casing & test

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

M.I. & R.U. Four Corners Drilling Company rig #7. Spudded a 12 1/4" hole at 9:45 P.M. 10-13-86. Drilled to 233'. Ran 5 jts. 9-5/8" OD, 36#, 8 Rd, L.S. casing (T.E. 213.84') set @ 226' RKB. Cemented with 125 sx (147.5 cf.) class "B" plus 2% CaCl₂. P.O.B. @ 4:15 AM 10-14-86. Circulated 1 bbl cement to surface. Pressure tested surface casing & BOP 600 psi for 30 minutes before drilling cement - held OK.

RECEIVED
OCT 21 1986
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

10-15-86

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 20 1986

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

NMOCG

BY 847