

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
Union Texas Petroleum

3. ADDRESS OF OPERATOR
375 U.S. Highway 64, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1695' FSL & 990' FEL

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, ET, GR, etc.)

6702' GR, 6714' KB

5. LEASE DESIGNATION AND SERIAL NO.

Jicarilla Contract 103

6. IF INDIAN, ALLOTTED OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

JICARILLA H

9. WELL NO.

92 12M

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde
Basin Dakta/W.H. Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 17-T26N-R4W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud & surface casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Union Texas Petroleum wishes to advise that the subject well was spud at 1:30 PM, 10/26/1986. A 12-1/4" hole was drilled to 320' KB. 9-5/8", 40.00#, K-55, Butt. casing was set at 320' KB and cemented to surface with 175 sxs (207 cu.ft.) Class "B" containing 2% CaCl2. Circulated 25 sxs (30 cu.ft.) to reserve pit. Nipple up BOP. Test BOP and casing to 1000 psi. All held OK. Drill 8-1/2" hole out of surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert C. Frank

TITLE Permit Coordinator

DATE 10/29/86

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NOV 03 1986

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY

6-2/14