

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. SF 080312  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<b>X</b>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 6, 19 60

INTEX-SOUTH PENN ESTE USL

Well No. #1-4 is located 1980 ft. from N line and 1980 ft. from E line of sec. 4

NW/4 of SE/4  
(1/4 Sec. and Sec. No.)

T. 26 N., R. 1 E.  
(Twp.) (Range)

N.M.P.M.  
(Meridian)

Puerto Chiquito  
(Field)

Rio Arriba  
(County or Subdivision)


New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 6959 ft. Grd.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Run Gamma Ray Neutron log total depth 2235'.
2. Place cement plug 2000' to total depth.
3. Pull 10 3/4" casing.
4. Plug with cement from 1200' to 1450'.
5. Plug with cement across surface pipe shoe.
6. Cement plug and marker in top of 13 3/8" surface pipe.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company INTEX OIL COMPANY

Address P.O. Box 1411

Bakersfield, California

FA 4-4956

By

RM Miller

Title

Production Manager