REPAIR WELL

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE.

ON THE REPLATE NO. 6. LEADE OF HONATA

SF 079958

							_
\sim	TI	CCC.	AND	DEDODEC	ON	MICHIC	•

1.		7. UNIT AGE STATE				
	THER Water Injection		Inti Unit			
2. NAME OF OPERATOR		8. FARM OR LEADE I	€A.M.E.			
Skelly Oil Comp	any					
3. ADDRESS OF OPERATOR		9. write no.				
· 1860 Lincoln St	reet, Denver, Colorado 80203	69				
4. LOCATION OF WELL (Report le See also space 17 below.)	ocation clearly and in accordance with any State requirements.	10, FIELD CHI : On .				
. At surface		Blat L	hower Gal lup -			
1980' FSL &	660' FEL Section 33-25N-10W	11, 850, 1, 8, 7 3 STREET - 19 AR				
			3-25N-10W			
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, OR, etc.)	12. COUNTY OR PAR	HH 13, STATE			
	6786' DF	San Juan	New Mexico			
16. Ch	eck Appropriate Box To Indicate Nature of Notice, Report,	or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:						
•	_ :					

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones penent to this work.)*

XX

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - (5266' - 5366') 100' plug across the Gallup Zone Perfs. 5304-5350'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1575' - 1725') 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- (885'- 985') 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

JUL 22 III	
\	
OIL COIL CONTROL Julpist. 397	j
DATE Julbist. 1912	

APPROVED BY CONDITIONS OF APPROVAL, IF ANY :

(This space for Federal or State office use)

18. I hereby certify that the foregoing is true and correct

Lead Clerk