

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved  
Bureau of Land Management  
5. LEASE INFORMATION AND SERIAL NO.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT CASE Bisti Unit	
2. NAME OF OPERATOR Skelly Oil Company		8. FARM OR LEASE NAME	
3. ADDRESS OF OPERATOR 1860 Lincoln Street, Denver, Colorado 80203		9. WELL NO. 50	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 660' FWL Section 28-25N-10W		10. FIELD AND TROOL, OR WILDCAT Bisti Lower Gallup	
14. PERMIT NO.		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Section 28-25N-10W	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6735' GR		12. COUNTY OR PARISH San Juan	
		13. STATE New Mexico	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☒CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of completion of any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for each well and zones pertinent to this work.)\*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - ( 5247'- 5347' ) 100' plug across the Gallup Zone Perfs. 5277-5318'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - ( 1545'- 1695' ) 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- ( 840'- 940' ) 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

18. I hereby certify that the foregoing is true and correct

SIGNED

*G. L. Biles*

TITLE

Lead Clerk

DATE

July 16, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side