

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate*
(Other instructions on re-
verse side)1. FIELD NO. 07-621
2. LEASE NO. 07-621
3. MINERAL NO.

4. IF INDIAN, AGENCY OR TRIBE NAME

Santa Fe-Brookhaven

7. UNIT AGREEMENT NAME

East Bisti Unit

8. FARM OR LEASE NAME

9. WELL NO.

52

10. FIELD AND POOL, OR WILDCAT

Bisti Lower Gallup

11. SEC., T., R., M., OR BLM AND
SURVEY OR AREA

Section 29-25N-10W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Skelly Oil Company

3. ADDRESS OF OPERATOR

1860 Lincoln Street, Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

800' FSL & 800' FWL Section 29-25N-10W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6730' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion or recompletion Report and Log for well.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable. Plans are to plug and abandon this well; plugging as follows:

First Plug - (5166'- 5266') 100' plug across the Gallup Zone Perfs. 5196-5236'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1495'- 1645') 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- (780'- 880') 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

18. I hereby certify that the foregoing is true and correct

SIGNED

L. L. Biles

TITLE

Lead Clerk

DATE

July 16, 1971

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE