16.

17.

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on verse side)

SUBMET IN TRIPLICATES

Form approved Russet Bureau No. 42 R1421. B. BEN E BOOKERSON A O REPLATE NO

B. IF I BIAT, ACROTTED OF TRIBE NAME.

078621-A

GEOLOGICAL SURVEY

21.12.12.037	MOTICEC	ANID	DEDODTE	ON	WELLC
SUNDKY	NOTICE2	ANU	REPORTS	ON	YY ELLO

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use "APPLICATION FOR PERMIT--" for such proposals.) Santa Fe 7. USET AGREEMENT NAME Tast Blatf Unit OTHER 2. NAME OF OPERATOR 8, FARSI OR LEARS NAME Skelly Oil Company 3. ADDRESS OF OPERATOR 9. WELL NO. 80203 1860 Lincoln Street, Denver, Colorado 44 LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) 10. PIELD AND DOOL, OR WILDCAT Bisti Lower Gallup At surface 11. SEC., T., R., M., OR REK. AND BURYEY OR AREA 2140' FWL & 1980' FSL Section 30-25N-10W Section 30-25N-10W

12. COUNTY OR PARISH 13. STATE 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. San Juan Hew Mexico 6619' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	BUBBEQUENT REPORT OF:		
TEST WATER SHUT-OFF FULL OR ALTER CASING MULTIPLE COMPLETE XXX SHOOT OR ACIDIZE ABANDON* REPAIR WELL CHANGE PLANS (Other)	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report results of multiple comparing or Vet and Completion or Recompletion Report and Acides)		
proposed work. If well is directionally drilled, give subsurface loca nent to this work.) • All depths shown are from Ground Level.	t details, and give pertinent dates, including estimated date of starting any tions and measured and true vertical depths for all markers and zones perti-		

This well has reached the economic limit and is no longer profitable Plans are to plug and abandon this well; plugging as follows:

First Plug - (5026' - 5126') 100' plug across the Gallup Zone Perfs. 5073-5080'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1355' - 1505') 150' plug extending downward from above the Fouitland coal section across the Pictured Cliffs Sand

Fourth Plug- (630' - 730') 100' plug extending from 50' above to 50' below the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

8. I hereby certify that the foregoing is true and correct SIGNED & B. Ha	TITLE Lead Clerk	INTE July 16, 1971
(This space for Federal or State office use)		a. Theresell a committee constitution of the second
APPROVED BYCONDITIONS OF APPROVAL IF ANY:	TITLE	DATE