

| | | | |
|---|--|--|--|
| | | | |
| X | | | |
| | | | |
| | | | |

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office SF
Lease No. 078021
Unit Brookhaven

RECEIVED

NOV 21 1958

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|--|--|---|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | X |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 20, 1958

Well No. 5-A is located 2080 ft. from N line and 560 ft. from E line of sec. 29
SW NW/4 Sec. 29 25N 10W NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blasi-Lower Gallup San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6661 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

11-17-58 Total Depth 5290'.

Ran 127 joints 5-1/2", 13.50#, J-55 Casing (5273') set at 5286' with
150 sacks regular cement, 150 sacks Pozmix, 4% Gel., 1/4# Floceals
per sack.

Held 1000#/30 Minutes.

Top of cement by temperature survey at 3900'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Products Company

Address Post Office Box 1565
Farmington, New Mexico

ORIGINAL SIGNED BY: JOSEPH E. KREGER

By _____

Title Petroleum Engineer