(May 1963)

16.

SUBMIT IN TRIPLICATE. INTERIOR (Other instructions on reBudget Bureau No. 42-R1424

DEIAITH			
C	14-20-603-	1383	
SUNDRY NOT (Do not use this form for propos Use "APPLICA	6. IF INDIAN, ALLOTTEE Window Rock Ka-Des-Pah		
OIL X GAS OTHER		7. UNIT AGREEMENT NAME East Bisti Unit	
2. NAME OF OPERATOR		8. FABM OR LEASE NAME	
Skelly Oil Company		· · · · · · · · · · · · · · · · · · ·	-
. ADDRESS OF OPERATOR 9. WELL NO.			
1860 Lincoln Street -	39	•	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		10. FIELD AND POOL, OR WILDCAT Bisti Lower Gallup	
1650' FNL & 330' FEL Section 25-25N-11W		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 25-25N-11W	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE	
	6681' GR	San Juan	New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING ABANDONMENT* X		
REPAIR WELL (Other)	CHANGE PLANS	(Other) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

All depths shown are from ground level.

7/17/71 MI & RU Aztec Well Service Unit. Pulled rods. Spotted cement plug 5217-5117'. Pulled 2" tubing. Worked 5-1/2" casing to free same. Rigged up blue jet and perforated 1584-1585' with 4 shots. Ran 2" tubing. Spotted cement plug 1585-1435'. Pulled tubing. Shot casing off at 1302'. Spotted cement plug 1352-1252', 50' inside of casing and 50' above casing stub. Pulled up casing. Spotted cement plug 790-690'. Pulled 5-1/2" casing (1307') 39 jts.

Spotted 10' cement plug in surface casing. Installed dry hole marker.

Completed P&A 7/27/71.



			DIST. 3
18. I hereby certify that the foregoing is true and correct SIGNED	t TITLE:	Lead Clerk	DATE 10-26-71
(This space for Federal or State office use)			
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE