

X			
	30		

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe, N.M.  
Lease No. AF 078063  
Unit Carson Unit


SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Report of Completion</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 22, 1958

Carson Unit  
Well No. 11-30 is located 660 ft. from N line and 660 ft. from W line of sec. 30  
MM 30 (1/4 Sec. and Sec. No.) 25N (Twp.) 11W (Range) NMPN (Meridian)  
Ditch (Field) San Juan (County or Subdivision)



Kelly Bushing  
The elevation of the XXXXXXXX above sea level is 6471 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

- 10-3-58 Run and cemented (4945') 4-1/2", 9.54, J-55 casing at 4955' with 150 sacks cement treated with 45 gal. (226 cu. ft. Portland cement, surface temperature 140° Formation temperature approx. 135°, estimated strength 1400 psi cement in place 36 hours + prior to test.) Pressure tested casing and plug with 1400 psi, OK.
- 10-4-58 Bullet perforated four 1/2" holes/ft. 4834-49, 4861-70, 4873-77, 4879-89, 4893-06, 4926-28, 4933-47.
- 10-5-58 Run tubing to 4942'. Made pressure survey.
- 10-6-58 Potted 200 gal. mud acid. Sand oil fractured with 50,000 gal. crude and 14/gal. sand (150 nylon core balls). Maximum pressure 2550 psi minimum pressure 2500 psi average rate 40.3 bbl/min.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. (OVER)

Company Shell Oil Company  
Address 705 W. Municipal Drive  
Farmington, New Mexico

Original signed by  
E. W. SHEPARD  
By B. W. Shepard  
Title Exploitation Engineer

10-7-58 Installed pump and recovered all sand and free oil, 1549 bbls.  
to  
10-10-58

10-19-58 INITIAL PRODUCTION. Pumping 280 B/D gross, 280 B/D clean,  
ent 0.1%, 55 MCF/D gas, OOH 290, completed 10-19-58.