10.

SUBMIT IN TRIPLICATES UNITED STATES DEPARTMENT OF THE INTERIOR COllege Instructions on re-

GEOLOGICAL SURVEY

SF 078621-A

12. COUNTY OR PAPERS, 13, 411.

of Burney No. 13 R1424

6. IL INDIAN. TLOTTER OR TRIBLENANCE

(De not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLIC		
OIL CAS OTHER	Water Injection	7. UNIT ACRES STATE OF THE BOOK STATE OF THE BOO
2. NAME OF OPERATOR	The state of the s	S. FARM OR TO THE NAME
Skelly 011 Company		
3. ADDRESS OF CPERATOR	,	9. WELL, NO.
1860 Lincoln Street	, Denver, Colorado 80203	22
4. LOCATION OF WILL (Report location See also space 17 below.) At surface	clearly and in accordance with any State requirements.*	10. FIRED AND LOOK, OR WILDCAT Bisti Lower Gallup
1980' FWL & 1980	'FSL Section 24-25N-11W	11. NRC., T., R., M., OR BLK. AND BURYET OR AREA
		Section 24-25N-17W
14. PERMIT SO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12, COUNTY OR PAPERSO, 13, 511.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

6546' DF

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:		
EST WATER BRUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	PAJAITING WITES	
RACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	AD1775 1 1 4 4 71 1/4	
SHOOT OR ACIOIZE		ABANDON*	XX	SHOOTING OR ACIDIZING	40.45 - 1354*	
Other)		CHANGE PLANS		(Other) (NOTE: Report results of mul- Completion or Recompletion b	Hiple completion in Well sport and L. form	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated in the of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all messeens and zones pertinent to this work.).

All depths shown are from Ground Level.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - (5023'- 5123') 100' plug across the Gallup Zone Perfs. 5086-5098'

Second Plug- 50' inside of the 5-1/2" casing and 50' above where casing is shot in two

Third Plug - (1320'- 1470') 150' plug extending downward from above the Fruitland coal section across the Pictured Cliffs Sand

Fourth Plug- (595'- 695') 100' plug extending from 50' above to 50' a low the bottom of the Ojo Alamo Sand

10 sacks of cement in top of surface casing with dry hole marker

					The same of the sa
	•	`			1 13 88 101
8. I hereby certify that the foregoing	s true and correct		······································		
SIGNED To L. Biles		TITLE	Lead Clerk		OK July 20, 1971
					
(This space for Federal or State off	ice ase)			•	
	1, 11,			F	
APPROVED BY		TITLE	 		DATE
CONDITIONS OF APPROVAL, IF	ANY:		• "		