UNITED STATES UNITED STATES SURMIT IN TRIPLICATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-

Budget Bureau No. 42 B1421.

GFOL	OGICA	L SURVEY
GLOL	JOGIUM	

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

6, IF INDIAN, ALLOTTEE OR TRIBE NAME

Use "A	PPLICATION FOR PERMIT—" for such proposals.)	
1.		7. UNIT AGREEMENT NAME
WELL X WELL OT	HER	East Bisti Unit
2. NAME OF OPERATOR		S. FARM OR LEASE NAME
Skelly Oil Compan	y	
3. ADDRESS OF OPERATOR	,	9. WELL NO.
1860 Lincoln Stre	et, Denver, Colorado 80203	16
4. LOCATION OF WELL (Report loc See also space 17 below.)	ation clearly and in accordance with any State requirements.	10. FIELD AND POOL, OR WILDCAT
At surface	and the second s	Bisti Lower Gallup
1987 2 ° FN	11. SEC., T., R., M., OR BLK. AND BURYRY OR AREA	
	Section 22-25N-11W	
14. PERMIT NO.	16. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	6426' GR 6436' KB	San Juan Nov. Nov.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF FRACTURE TREAT BHOOT OR ACIDIZE		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON®		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL ALTERING CASING ABANDONMENT®	
REPAIR WELL (Other)		CHANGE PLANS		(Other) (Note: Report results of me Completion or Recompletion	altiple completion on Well Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent.

This well has reached the economic limit and is no longer profitable to operate. Plans are to plug and abandon this well; plugging as follows:

First Plug - 100' plug across Gallup Zone perforations 4910-4946'

Second Plug - 50' inside the 5-1/2" casing and 50' above where casing is shot in two Third Plug - 150' cement plug extending downward from above the Fruitland Coal section across the Pictured Cliffs Sand

Fourth Plug - 100' plug at bottom of Ojo Alamo Sand (unless surface casing is set through the Ojo Alamo Sand)

10 sacks of cement in top of surface casing with dry hole marker



	.:				
18. I hereby certify that the foregoing by true and confect SIGNED	TITLE D	istrict Oper	ations Supt.	DATE June	10, 1971
(This space for Federal or State office use)				_	
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE _			DATE	