

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land C	office Farmington	
	vo. 078154	
	Govt Ross	

NOTICE OF INTENTION TO DRILL.	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Running
	Production Casing X
(INDICATE ABOVE BY CHECK MAR	K NATURE OF REPORT, NOTICE, OR OTHER DATA)
	June 26 , 19 56
Govt Ross  Vell No. 2 is located 660 ft. from  NE NE Sec. 24 25N  (4 Sec. and Sec. No.) (Twp.)	m. $\begin{bmatrix} N \\ XX \end{bmatrix}$ line and $560$ ft. from $\begin{bmatrix} E \\ XX \end{bmatrix}$ line of sec. 24
(14 Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
Sisti-Gallup San Juan C	ounty NM or Subdivision) (State or Territory)
itate names of and expected depths to objective sands; show s ing points, and all	AILS OF WORK  izes, weights, and lengths of proposed casings; indicate mudding jobs, cemen other important proposed work)
to 5155' with heavy mud and 135 sax at 5153' KB. Casing equipped w/Bake centralizers; and cemented with 135 of 1000 PSI. Ran temperature survey	cement. Ran $5\frac{1}{2}$ ", 15.5#, J-55 casing landed er Shoe FloatCollar, Scratchers, and
to 5155' with heavy mud and 135 sax at 5153' KB. Casing equipped w/Bake Centralizers; and cemented with 135 a/1000 PSI. Ran temperature survey 410' KB.  I understand that this plan of work must receive approval a company The British-American Oil 1 Address Box 180	sax 3% Gel cement. Pumped plug to 5086' Ki and found top of cement behind casing at  REFERENCE 23 456 OIL CON COMPANIES. 3  Producing Company
to 5155' with heavy mud and 135 sax at 5153' KB. Casing equipped w/Bake centralizers; and cemented with 135 a/1000 PSI. Ran temperature survey 410' KB.  I understand that this plan of work must receive approval.	cement. Ran 5½", 15.5#, J-55 casing landed er Shoe FloatCollar, Scratchers, and sax 3% Gel cement. Pumped plug to 5086' Ki and found top of cement behind casing at Coll Con oil Con
to 5155' with heavy mud and 135 sax to 5153' KB. Casing equipped w/Bakentralizers; and cemented with 135 1/1000 PSI. Ran temperature survey 410' KB.  I understand that this plan of work must receive approval in the British-American Oil 1 address Box 180	cement. Ran 5½", 15.5#, J-55 casing landed er Shoe FloatCollar, Scratchers, and sax 3% Gel cement. Pumped plug to 5086' Ki and found top of cement behind casing at Collar Con Collar

en la completa de la Televación de la completa del completa de la completa del completa de la completa del la completa de la c



o5 0 6 . 1 1 1