

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>XXX</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICODenver, Colorado  
(Place)March 22, 1960  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the British-American OilProducing Company

(Company or Operator)

FED. ROSSWell No. 2NE  $\frac{1}{4}$ NE  $\frac{1}{4}$ of Sec. 24T. 25 NR. 13 W

NMPM,

Lower Gallup

(40-acre Subdivision)

San Juan

County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)


This well completed as a lower Gallup sand producer in July 1956, with an initial potential of 20 barrels oil and 3 barrels water per day. By March 1959 production had decreased to 2 barrels oil and 1 barrel water per day, which is below the economic limit and since there is no other possible pay zone it is proposed to plug and abandon this well by filling hole with heavy mud with a 150 sax cement plug in bottom of well to cover the perforations at 5020-4984, shoot 5½" casing off at approximately 1500' and pull, spot a 200' cement plug at 1525 to 1300 to cover the Picture Cliffs formation, spot 20 sax cement plug in bottom of surface casing at 250-200, a 10 sax cement plug in top of surface casing, erect a dry hole marker, level and abandon location.

Approved MAR 25 1960 19  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION  
Original Signed Emery C. Arnold  
By \_\_\_\_\_  
Title Supervisor Dist. # 3

The British-American Oil Producing Co.Original Signed By \_\_\_\_\_  
Company or OperatorBy Thomas M. HoganPosition District Superintendent

Send Communications regarding well to:

Name The British-American Oil Prod CoAddress Box 180; Denver 1, Colorado

STATE OF NEW MEXICO		
OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
NUMBER OF COPIES RECEIVED		3
DISTRIBUTION		
SANTA FE		1
FILE		1
U.S.G.S.		
LAND OFFICE		
TRANSPORTER	OIL	
	G-S	
PERORATION OFFICE		
OPERATOR		1