2-50 PRINTED IN U. S. A. 3-58 Preprint **M 1718-P 5-59

SHELL OIL COMPANY

Carson Unit 31-24

Bisti

DRILLING REPORT FOR PERIOD ENDING

24 (SECTION OR LEASE)

(FIELD) San Juan, New Mexico (COUNTY)

3-28-60

T25N R12W (TOWNSHIP OR RANCHO)

DAY	DEPTHS					
	FROM TO		REMARKS			
			Location: 660'S and 1980'W of NE corner Sec. 24, T25N, R12W, NMPM, San Juan County, New Mexico			
			Elevations: DF 6436.7° GR 6h29.0° KB 6438.2°			
3-21 To 3-22	0	2584	Spudded 8:00 A.M. 3-21-60. Ran and cemented (96:) 8-5/8", 32#, J-55 casing at 105: with 100 sacks cement treated with 2% calcium chloride. Good returns to surface. Flanged up and waited on cement. Pressure tested casing and BOP with 700 psi. OK.			
3-23 To 3-26	2584	4885	Drilled 2301?.			
3-27	4865	5030	Drilled 145°. Ran Micro-SP log.			
3-28	5030 (T D)		Ran and cemented (5020') 4-1/2", 9.5#, J-55 casing at 5029' with 150 sacks cement treated with 4% gel. Displaced with oil. Held 1500 psi, OK. Released rig 4:15 A.M. 3-28-60.			
			Checked BOP daily Mud Summary Wt 9.2-9.8 #/gal. Vis 44-120 sec. WL 5.2-8 ec FC 2/32" Contractor: Brinkerhoff Drilling Co. Co. Pusher: W. C. Thompson			
	C	NOITION	AT BEGINNING OF PERIOD			
	HOLE	c	ASING SIZE DEPTH SET			

0	CASING SIZE	DEPTH SET
то		
1		

SHELL OIL COMPANY

Carson Unit 31-24

Bisti

San Juan, New Mexico

DRILLING REPORT FOR PERIOD ENDING

4-15-60

24
(SECTION OR LEASE)
T25N R12W

	(COUN	TY)	T25N R12W (TOWNSHIP OR RANCHO)			
DAY	DEPTHS					
	FROM	то	REMARKS			
3-29	5030 (TD)		Perforated four 1/2% moles/ft. 4876-94, 4919-24, 4943-51, 4960-68, 4976-66.			
3 - 30			Spotted 200 gal. mad acrd. Sand oil fractured with 50,000 gal. crude, 1#/gal. sand. Dropped 100 balls in 3 stages, 100 psi increase after 1st 40 ball stage and 50 psi increase after each of next two 30 ball stages. Maximum pressure 2400 psi, average rate 30 bbls/min.			
3~31 To 4~2			Cleaned out frame sand. Ran 2-3/8" tubing to 4880, ran rods and pump.			
4-3 To 4-14			Pumped and recovered all road and frac oil, 1598 bbls.			
4-15			INITIAL PRODUCTION Pumping 197 B/D gross, 196 B/D clean, cut 0.4%, 643 MCF/D gas, GOR 3280. Completed 4-15-60			

	HOLE		CASING SIZE	DEPTH SET
SIZE	FROM	то		
2-1/4	0	106	8-5/8**	1058
7-7/8	106	5030	4-1/2"	5029*
		<u> </u>		
DRILL	PIPE 4	1/2		