

(SUBMIT IN TRIPLICATE)

Indian Agency                     

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Allottee Tribal Lands

Lease No. 11-20-603-1285

	13	
X		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	May 14 1959
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	X
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 12, 1959

Well No. 2-18 is located 660 ft. from DK line and 1930 ft. from W line of sec. 18

S. 18  
(1/4 Sec. and Sec. No.)

25N  
(Twp.)

11W  
(Range)

N18°W  
(Meridian)

Histi  
(Field)

San Juan  
(County or Subdivision)

New Mexico  
(State or Territory)

Kelly Dushing


The elevation of the shut-in above sea level is 6109 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 4-28-59

4-28-59 Ran and cemented (96') 8-5/8", 21#, J-55 casing at 106' with 100 sacks, 120 cubic feet Portland cement treated with 2% calcium chloride, to surface temperature 90°F., formation temperature 70°F.+. Estimated strength after 12 hours 1100 psi. Flanged up and waited on cement. Tested BOP and casing with 700 psi, OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations be commenced.

Company Shell Oil Company

Address 705 West Municipal Drive

Farmington, New Mexico

By

B. W. Shepard

Title Exploitation Engineer