

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa Fe, New MexicoLease No. ST-073056

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 17, 1956

Well No. 12-15 is located 1900 ft. from [N] line and 660 ft. from [E] line of sec. 15SW 1/4 NW 1/4 15 25 N 12 W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Dist 1
(Field)Santa Fe
(County or Subdivision)New Mexico
(State or Territory)The elevation of the Kelly Bushing deck floor above sea level is 6226.31 ft.


DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 5-11-56

5/11-13/56 Ran and cemented 5 5/8", 210', J-55, ST & C Spring casing at 223' with 100 sacks treated construction cement, 112 #/cu. ft. slurry. Waited on cement and flanged up. Tested casing with 700 psi for 30 min., OK.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SHELL OIL COMPANY
Address 33 RICHARDS STREET
SALT LAKE CITY, UTAHBy B. W. Chapin
Title Exploitation Engineer

SCHLUMBERGER WELL SURVEYING CORPORATION
HOUSTON, TEXAS



COUNTY SAN JUAN, N.M.	
FIELD or LOCATION BISTI GALLUP	
WELL GOV'T. #12-15	
COMPANY SHELL OIL COMPANY	
COMPANY SHELL OIL	Location of Well
WELL GOV'T. #12-15	660' FR E/L
FIELD BISTI GALLUP	1980' FR S/L
LOCATION SEC. 15-25N-12W	SEC. 15-25N-12W
COUNTY SAN JUAN	TEMP ES ML GRN)
STATE NEW MEXICO	Elevation: D.F.:
FILING No.	K.B.:
	or C.L.:
Date 5-22-56	Time Started 2400
First Reading 4683	Time Finished 1000
Last Reading 2550	Time Started
Footage Measured 2233	Time Finished
Max. Depth Reached 4684	
Bottom Driller 4900	
Hole Size 2 1/2	
Casing Size 5 1/2	
Depth Datum KB	
Mud Data Nature MUD & WATER	Resistivity F
Fluid Level	
Max Temp 159	
Cementation Date Date 5-21	Time Started
Cementation Date Date	Time Finished
A-Cement Top Determination	
1) Date Pressure Released 5-21-56	Time Released 1030
2) Amount Cement 350	SAOKS REG
3) Calculated Top 2700	
4) Depth of Plug 4500	
B-Location of Oil and Gas	
1) Casing Shoe Driller 4900	
2) Date Drilling Stopped	
Truck No. 1527 FARM	Time Stopped
Recorded By DENNIS	
Witnessed By CHRISTIANSEN	

REMARKS CEMENT TOP DETERMINATION

DEPTH 2"=100'

F.R. 2550'

TEMPERATURE ° F.
10°F. = 10 DIVISIONS

