

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well ☒ Oil Well ☐ Gas Well ☐ Other	5. Lease Designation and Serial No. SE078228-B
2. Name of Operator Dugan Production Corp.	6. If Indian, Allottee or Tribe Name
3. Address and Telephone No. P.O. Box 420, Farmington, NM 87499 (505) 325-1821	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FNL - 660' FWL Sec. 15, T25N, R11W, NMPM	8. Well Name and No. Bedford 1
	9. API Well No. 30-045-05414
	10. Field and Pool, or Exploratory Area Bisti Gallup
	11. County or Parish, State San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
☐ Notice of Intent	☒ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment Notice	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☐ Other
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut-Off
	☐ Conversion to Injection
	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged well as follows:

1. Spot 34 cu.ft. class "B" cement plug @ 4700'. Gallup plug 4450' - 4700'.
2. Perforate 5½" casing @ 2015'. Spot 55.5 cu.ft. class "B" cement plug. Displace cement to 1815'. Mesa Verde plug 1815' - 2015'.
3. Perforate 5½" casing @ 1297'. Spot 119 cu.ft. class "B" cement w/4½ gel. Displace cement to 910'. Pictured Cliffs - Fruitland plug 910' - 1297'.
4. Perforate 5½" casing @ 475'. Circulate cement to surface through bradenhead (240 cu.ft. class "B" w/4½ gel + 29.5 cu.ft. class "B" cement). Ojo Alamo - surface plug 0' - 475'.

Job complete 3/22/95.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander Title Operations Manager Date 3/24/95
(This space for Federal or State office use)Approved by _____ Title _____ Date _____
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD

APPROVED

MAR 27 1995

DISTRICT MANAGER