Budget Bureau	No.	42-R358.
Approval expire	s 12	-31- 60 .

FOE ()	Peb. 1	951)	1	
			X	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Sar	ita.	Pg	
Lease No	SF	0/8	475	.
Unit				

SUNDRY NOTICES AND REPORTS ON WELLS AND 2 6 1959

NOTICE OF INTENTIO	ON TO DRILL		1 11			UT-OFF	
MOTIOE OF INTENTIO	ON TO CHANGE PLANS		2 13			OR ACIDIZING	
	ON TO TEST WATER SHL		1 11			CASING	1 1
_	ON TO RE-DRILL OR RE		i li			G OR REPAIR	
	ON TO SHOOT OR ACIDI		11			IENT	1 1
	ON TO PULL OR ALTER		SUPPLE	MENTARY WEL Charles & & &	LHISTORT Sp ort of	Surface Cas	dne X
NOTICE OF INTENTI	ON TO ABANDON WELL.				<u> </u>		
	(INDICATE ABO	VE BY CHECK MAR	K NATURE OF RI	EPORT, NOTIC	E, OR OTHER DA	ITA)	
	·				eo anst		10 2
				·	ÿ -2 4	L	, 19.22
henson-Fede /ell No1	ral is located	1659_ft. fro	$\mathbf{m}_{-} \begin{bmatrix} \mathbf{N} \\ \mathbf{S} \end{bmatrix}$ line	and 155	1 ft. from	$\left\{ \frac{\mathbf{E}}{\mathbf{W}} \right\}$ line of s	ec. <u>17</u>
		25-% (Twp.)	(Range)	3	[설문설 Meridian)		
	ta	San J	MD			tate or Territory)	
(Field)	Found the starting from	(00444)	,		(6	tate of lettion;	
		DETA	ILS OF V	VORK			
itate names of and e	xpected depths to object	tive sands; show a ing points, and al	ilzes, weights, as I other imports:	nd lengths of	proposed casin rork)	gs; indicate muddir	ng jobs, c eman
Spudded well	w/a rotary : 9 9/8° 0. D. it cement w/20 11:30 %. 4. 08	ig on 3-16	-59. Ori 40 surfac	nd lengths of nt proposed w lled 13 oe casin	3/4" ho go 2021 circula 8-13-74 RILL ALC 2	Le to 212', Comented ted to surf w/1000/ for Living 17 1959 IN. COM	Set pipe ace.
Spudded well jts of new m/150 sx mea Plug down w minutes. He	w/a rotary : 9 9/8° 0. D. it cement w/20 11:30 %. 4. 08	ig on 3-16 32.30# %- calcium 6 8-15-59.	-59. Ori 40 surfac hloride. Tested	lled 13 ce casin Cement	3/h" ho g 202' circula 8-19-70' RLL ALL OHL CO	Le to 212', Cemented ted to surf w/1000/ for 1/1959 IN. CON' ST. 3	Set pipe ace.
Spudded well jts of new 1/150 sx new Plug down we minutes. Se	w/a retary : 9 5/8" 0. D. it cement w/2: 11:30 %. %. 0:	ig on 3-16, 32, 30% %-6, caldium 6, 8-16-59.	-59. Ori 40 surfac hloride. Tested	lled 13 ce casin Cement	3/h" ho g 202' circula 8-19-70' RLL ALL OHL CO	Le to 212', Cemented ted to surf w/1000/ for 1/1959 IN. CON' ST. 3	Set pipe ace.
Foundard wells jts of new 150 sx new 1150 sx new 1150 sx new 150 s	w/a retary : 9 5/8" 0. D. it coment w/2: 11:30 %. %. 0: itd 0. %.	ig on 3-16, 32, 30% %-6, caldium 6, 8-16-59.	-59. Ori 40 surfac hloride. Tested	lled 13 ce casin Cement	3/4" ho 202' circula 5-13 Fr	Le to 212', Cemented ted to surf w/1000/ for 1/1959 IN. CON' ST. 3	Set pipe ace. 30

U. S. GOVERNMENT PRINTING OFFICE: 1958 O -463339
