

DRILLING REPORT
FOR PERIOD ENDING

10
(SECTION OR LEASE)
T25N R12W
(TOWNSHIP OR RANGE)

San Juan, New Mexico
(COUNTY)

11-11-58

DAY	DEPTH		REMARKS
	FROM	TO	
			Location: 2010' S and 1931' W of NE corner Sec.10, T25N, R12W, San Juan County, New Mexico.
			Elevations: DF 6237.9 GR 6230.2 KB 6239.1
11-7 to 11-8	0	2060	Spudded 1:30 P.M. 11-7-58. Ran and cemented (96') 8 5/8" 24#, J-55 casing at 106' with 100 sacks cement treated with 2% calcium chloride. Good returns to surface. Flanged up and waited on cement. Pressure tested casing and BOP with 500 psi, OK.
11-9 to 11-12	2060	4760	Drilled 2701'.
11-13	4761	4930	Drilled 174'. Ran Electrical Survey and Microlog.
11-14	4935	TD	Ran and cemented (4920') 4 1/2", 9.5#, J-55 casing at 4930' with 150 sacks cement treated with 4% gel. Displaced with oil. Released rig 7:45 A.M. 11-14-58.
			Checked BOP daily.
			Mud Summary Wt. 9-9.8#/gal. Vis. 30-70 Sec. WL 6-7.6 CC FC 2/32"
			Contractor: Brinkerhoff Drilling Co. Drillers: C. Adams E. Babcock J. Speaker
			Co. Pusher: B. Ferguson

CONDITION AT BEGINNING OF PERIOD				
HOLE			CASING SIZE	DEPTH SET
SIZE	FROM	TO		
DRILL PIPE SIZES				

C. Bremer

East
(FIELD)
San Juan, New Mexico
(COUNTY)

DRILLING REPORT
FOR PERIOD ENDING
12-1-58

10
(SECTION OR LEASE)
T25N R12W
(TOWNSHIP OR RANGE)

DATE	DEPTHS		REMARKS
	FROM	TO	
11-10	4935	TD	Bullet perforated four 1/2" holes/ft. 4798-4840, 4868-4878, 4882-4898.
	4930	PETD	
11-11			Made 12 hour pressure survey.
11-16			Spotted 200 gal mud acid on perforations. Sand oil fractured with 50,000 gal crude, 1#/gal. sand and 250 nylon core balls. Pressure increased from 2600 psi to 2700 psi after dropping balls. Break down pressure 2600 psi, maximum pressure 2700 psi, minimum pressure 2600 psi. Flushed with 230 bbls crude.
11-17			Bailed frac sand from 4865 to 4930.
11-18			Ran tubing to 4800', pump and rods.
11-19			Pumped and recovered all load and frac oil, 1618 bbls.
12-1			INITIAL PRODUCTION Pumped 24 hours, 178 B/D gross, 178 B/D clean, cut 0.1%, Gas 107 MCF/D, GOR 770, TP 90, CP 400, completed 12-1-58.

CONDITION AT BEGINNING OF PERIOD				
DATE	HOLE		CASING SIZE	DEPTH SET
	FROM	TO		
12-1	0	115	8 5/8	106'
7 7/8	115	4935	4 1/2	4930'
DRILL PIPE SIZES		1 1/2		

C. Bremer

SIGNED