

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____

Allottee _____

Lease No. 11-77-409-25

	X	
Sec. 9		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

RECEIVED
JAN 27 1960
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 26, 1960

Well No. 2 is located 231 ft. from N line and 2210 ft. from W line of sec. 9

23 1/4 21 1/4 19 1/4 Sec. 9 25 N 19 W 11-77-409-25
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Alacat New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5943 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is intended:

To set 30 sack reg. cement plug from 1300 ft. to 1546 ft. - 4" casing
Fill with mud from 425 ft. to 1300 ft.
Set 45 sack reg. cement plug from 200 ft. to 425 ft. - 6 3/4" hole
Fill with mud to surface pipe from 80 ft. to 200 ft.
Set 15 sack reg. cement plug from 0 ft. to 80 ft. on 2 1/2" x 6 ft.
pipe marker in top of surface pipe.
Clean up location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Drilling & Coring Exploration Co.

Address 1809 Laguna

Farmington, New Mexico

By Carl E Hazmon

Title Partner



