F	E (F	m 'eb. 19	321 £	<b>5</b>	30	O	VE	)
	ı		1	ЮЦ	2	7 1	956	
		. 3	JE	R R	/ W	. <b>\</b> CT	ONG ENGINEE	D
				3				

(SUBMIT IN TRIPLICATE)

## UNITED STATES EPARTMENT OF THE INTERIOR

Land Office Louis No. 078156-4 Unit Gov. Sale

GEOLOGICAL SURVEY

OTICE OF INTENTION TO DRILL	SUBSEQUENT IS SU	
		<b>34.9</b> , 19
ell No. 2 is located.	1990 ft. from. $\binom{N}{2}$ line and	ft. from line of sec. 3
(½ Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)
(1/2 Sec. and Sec. No.)	Sen Juan	(State or Territory)
(Field)	(County or Subdivision)	
	4337	t. OL
	l and and larval is	11.
ne elevation of the derrick flo	or above sea level is	It.
	DETAILS OF WOR	rt. RK
ate names of and expected depths to obj	DETAILS OF WOR	ngths of proposed casings; indicate mudding jobs, co oposed work)
Dellied 13-VA hale to object the last of t	DETAILS OF WOF  ective sands; show sizes, weights, and let ing points, and all other important pr  200 KB. Ram S joints,  mandal with 175 can 25  good returns to carface g with 500 f for 30 mix	ngths of proposed casings; indicate mudding jobs, co opposed work)  9-5/8", 32-30f, N-40 Coming GACL regular common. Displace Values 24 hours, drilled com
Dellied 13-1/4" hele to object the landed of 234" IS and occurred to 234" IS with consent and touted continues.	DETAILS OF WOF setive sands; show sizes, weights, and let ing points, and all other important pr  240° IR. Ram 5 joints, amended with 175 and 25 good returns to sarface 8 with 500 f for 30 min	ngths of proposed casings; indicate mudding jobs, cooposed work)  9.5/8", 32.30f, 31.40 Cooping CACL regular common. Bisplace 1. Valted 24 hours, drilled on makes. Held OK.
I understand that this plan of work m  Company The British-is	DETAILS OF WOF  ective sands; show sizes, weights, and let ing points, and all other important pr  200 KB. Ram S joints,  mandal with 175 can 25  good returns to carface g with 500 f for 30 mix	ngths of proposed casings; indicate mudding jobs, cooposed work)  9.5/8", 32.30f, 31.40 Cooping CACL regular common. Bisplace 1. Valted 24 hours, drilled on makes. Held OK.
I understand that this plan of work m	DETAILS OF WOR  ective sands; show sizes, weights, and let ing points, and all other important pr  200 KB. Ram & joints.  managed with 175 can 25  good returns to carface  with 500 f for 30 mix  must receive approval in writing by the G	ngths of proposed casings; indicate mudding jobs, co opposed work)  9-5/8", 32-30f, R-40 Cosing CACL regular connect. Bisplace L. Taited 24 hours, drilled on mass. Held CK.