

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-330-C for such proposals.)

1. Oil ☐ well ☐ gas ☐ well ☐ other ☐
2. NAME OF OPERATOR
Nixon Development Company
3. ADDRESS OF OPERATOR
P.O. Box 2810, Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FWL, 1980' FNL, 5-25-12
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☒
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or change of Form 9-330.)

RECEIVED

SEP 13 1983

SEP 14 1983

FARMINGTON RESOURCE AREA OIL CONTROL DIV.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Squeezed well's perforations with 175 sacks Class B cement. Cleaned out hole to 4844'. Reperforated 4810'-22' with 48 holes. Acidized with 1000 gallons 15% HCl acid. Well on injection through 2-7/8" tubing. Packer set at 4751'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED William H. Watson TITLE Petroleum Engineer DATE 9/2/83

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

SEP 13 1983

WHDCC

FARMINGTON RESOURCE AREA

BY RB