Form	9-8318
(Feb	. 1951)

*	 	
	 !	!

(SUBMIT IN TRIPLICATE)

Land Office Santa 70 UNITED STATES R Unit -----

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

		II	WATER CHIEF OFF	X
OTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF	WATER SHUT-OFF	
TICE OF INTENTION TO CHANGE I		SUBSEQUENT REPORT OF	SHOOTING OR ACIDIZING	
ICE OF INTENTION TO TEST WAT	ER SHUT-OFF		ALTERING CASING	
TICE OF INTENTION TO RE-DRILL	OR REPAIR WELL		RE-DRILLING OR REPAIR	
TICE OF INTENTION TO SHOOT O	R ACIDIZE	SUBSEQUENT REPORT OF		
TICE OF INTENTION TO PULL OR	ALTER CASING.	SUPPLEMENTARY WELL F	HISTORY	
TICE OF INTENTION TO ABANDON	WELL			
INDIC	ATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, C	R OTHER DATA	
		× 21.		19.56
N.W. Pederal *C* le	ase ated 1983 ft. from.	-	ft. from $\left\{ egin{array}{c} lackbox{U} \ lackbox{V} \end{array} ight\}$ line of second	
11110.	Andrine	100 000	(. ,	
i/L Mi/L	(Twp.)	(Range) (Me	ridian)	
(1/4 Sec. and Sec. No.)	San Juan		Hey Hext se	
(Field)	(County o	or Subdivision)	(State or Territory)	
e elevation of the derric	k floor above sea lev	vel is 6199 ft.		
C CICTAGOLO OL CLIC				
	DETAI	ILS OF WORK		- iohs cemel
	DETAI	ILS OF WORK	oposed casings; indicate mudding k)	g jobs, cemer
ate names of and expected depths	DETAI to objective sands; show siz ing points, and all o	ILS OF WORK tes, weights, and lengths of prother important proposed wor	177* w/200 ax of e	met.
We drilled a 15th Coment circulated to set the cog we then drilled an	DETAI to objective sands; show size ing points, and all of the sure tested to 12% When hole to 5% After units for 30 min with	ils of Work tes, weights, and lengths of prother important proposed work Set 10-3/h cag rface. After wai of for 30 min wit oze and set 5025 ing his has for the	oposed casings; indicate mudding to the set the case to set the case. The top of the	net. p comen pre. W not of ng was
We crilled a 15% Cement circulated to set the ceg we then drilled an 1:1 Possix w/25 in the annuls is	DETAI to objective sands; show size ing points, and all of the sure is tested to 12% When hole to 5% The hole to 5% The sure is tested to 12% The hole to 5% The sure is tested to 12% The hole to 5% The sure is tested to 12% The	in writing by the Geological S	ting 2h hrs for the h no lose in press. It of 5% asg w/175 as the curre. The top of the RELET	mt. permenter. W mx of my was
We drilled a 15" Cement circulated to set the cog we then drilled an 1:1 Posmix w/25 tested to 1500 in the annuls is	DETAI to objective sands; show size ing points, and all of the sure is tested to 12% When hole to 5% The hole to 5% The sure is tested to 12% The hole to 5% The sure is tested to 12% The hole to 5% The sure is tested to 12% The	in writing by the Geological S	ting 2h hrs for the h no lose in press. It of 5% asg w/175 as the curre. The top of the RELET	mt. permenter. W mx of my was
We crilled a 15" Cement circulated to set the cog we then drilled an 1:1 Possix w/25 in the annuls is I understand that this plan of the company Sure w/25 in the annuls is	DETAI to objective sands; show size ing points, and all of the sure is tested to 12% When hole to 5% The hole to 5% The sure is tested to 12% The hole to 5% The sure is tested to 12% The hole to 5% The sure is tested to 12% The	in writing by the Geological S	ting 2h hrs for the h no lose in press. It of 5% asg w/175 as the curre. The top of the RELET	net. p comen pre. W not of ng was
We crilled a 15% Coment circulated to set the cog we then drilled an 1:1 Posmix w/25 tested to 150% in the annuls is	DETAI to objective sands; show size ing points, and all of the sure is tested to 12% When hole to 5% The hole to 5% The sure is tested to 12% The hole to 5% The sure is tested to 12% The hole to 5% The sure is tested to 12% The	in writing by the Geological S	ting 2h hrs for the h no lose in press. It of 5% asg w/175 as the curre. The top of the RELET	net. p comen pre. W not of ng was
We crilled a 15" Cement circulated to set the cag we then drilled an 1:1 Possix w/25 in the annals is I understand that this plan of the company Susaway 110- ddress Box 128	DETAI to objective sands; show size ing points, and all of the sure in the sure is tested to 12%. The hole to 50 pel. After with 10 pel. After wi	in writing by the Geological S	ting 2h hrs for the h no lose in press. It of 5% asg w/175 as the curre. The top of the RELET	net. p comen pre. W not of ng was
We crilled a 15" Cement circulated to set the cog we then drilled an 1:1 Possix w/25 tested to 1500/ in the annuls is	DETAI to objective sands; show size ing points, and all of the sure in the sure is tested to 12%. The hole to 50 pel. After with 10 pel. After wi	in writing by the Geological S	ting 2h hrs for the h no lose in press. It of 5% asg w/175 as the curre. The top of the RELET	mt. permenter. W mx of my was

