

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

P. C. Box 965 Parmington, New Mexico

February 13, 1956

Benson-Montin LO54 West Broadway Farmington, New Mexico

Re: Santa Fe 080375-C

Gentlemen:

Receipt is acknowledged of your "Notice of Intention to Drill" dated February 10, 1956 covering your well No. 5 Sheets in SWA NE' sec. 1, T. 25 N., R. 8 W., N. H. P. M., San Juan County, New Mexico, Ballard poel.

Your proposed work is hereby approved subject to compliance with the provisions of the "Oil and Gas Operating Regulations" revised May 25, 1942, a copy of which will be sent to you on request, and subject to the following conditions:


- 1. Drilling operations so authorized are subject to the attached sheet for general conditions of approval.
- 2. Furnish copies of all logs.

Very truly yours,

(Orig. Sgd.) P. T. McGRATH

P. T. McGrath District Engineer

PTMcGrath:ac





(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa Fe
Lease No	090375- C
Unit	Sheets

NE/4 of Section 1 is besignated Drilling Unit

NOTICE OF INTENTION TO DRILL	SUBSEQUI	ENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	1 1	ENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF) !	ENT REPORT OF ALTERING CASING	533
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUI	ENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUI	ENT REPORT OF ABANDONMENT	32
NOTICE OF INTENTION TO PULL OR ALTER CASING	1 11	ENTARY WELL HISTORY	Will a
NOTICE OF INTENTION TO ABANDON WELL	1 1	<u> </u>	LAL MENTON
		Ω_{i}	12 M. M.
(INDICATE ABOVE BY CHECK N	MARK NATURE OF REP	PORT, NOTICE, OR OTHER DANS	(*)
		February 10.	1054
Vell No. 5 is located 1470 ft. SW/4 NE/4 Sec. 1 25N (Y Sec. and Sec. No.) (Twp.)	(Range)	N. N. P. N. (Meridian)	H
Ballerd Sa (Field) (Co	n Juan	New Mexico	
tate names of and expected depths to objective sands; sho	TAILS OF WO	liengths of proposed casings; indicate mudd	
Pictured Cliffs Sand test. Est: Surface: Casing: 90° of 8-5/8"	owsizes, weights, and i all other important imated total 000 24* J-55.	Hengths of proposed casings; indicate mudd t proposed work) depth 2400*, camented to surface,	
Pictured Cliffs Sand test. Est: Surface: Casing: 90° of 8-5/8"	owaizes, weights, and i all other important imated total 00 24* J-55, 2300* of 5-1 100 sacks.	lengths of proposed casings; indicate mudder proposed work) depth 2400°, cemented to surface, /2° 00 15.5* J-55, producing section will	
Pictured Cliffs Sand test. Est: Surface: Casing: 90° of 8-5/8" (Production ": Approximately a cemented with ! If commercial production is indibe shot with nitroglyceria and/e	imated total 24* J-55, 2300* of 5-1 100 sacks, icated, the or sandfrace	lengths of proposed casings; indicate mudder proposed work) depth 2400°, cemented to surface, /2° 00 15.5* J-55, producing section will- d. Geological Survey before operations may be	ling jobe, cement-
Pictured Cliffs Sand test. Est: Surface: Casing: 90° of 8-5/8° (Production " : Approximately comented with : If commercial production is indibe shot with nitroglyceria and/o	imated total 24* J-55, 2300* of 5-1 100 sacks. icated, the or sandfrace	lengths of proposed casings; indicate mudder proposed work) depth 2400°, cemented to surface, /2° 00 15.5* J-55, producing section will- d. Geological Survey before operations may be	ling jobe, cement-
Pictured Cliffs Sand test. Est: Surface: Casing: 90° of 8-5/8" (Production ": Approximately a cemented with ! If commercial production is indibe shot with nitroglyceria and/e	imated total 24* J-55, 2300* of 5-1 100 sacks. icated, the or sandfrace	lengths of proposed casings; indicate mudder proposed work) depth 2400°, cemented to surface, /2° 00 15.5* J-55, producing section will- d. Geological Survey before operations may be	ling jobe, cement-
Pictured Cliffs Sand test. Est: Surface: Casing: 90° of 8-5/8° (Production " : Approximately comented with : If commercial production is indibe shot with nitroglyceria and/o	imated total 1 J-55, 2300 of 5-1 160 sacks. 1 cated, the or sandfrace	lengths of proposed casings; indicate mudder proposed work) depth 2400°, cemented to surface, /2° 00 15.5* J-55, producing section will- d. Geological Survey before operations may be	ling jobe, cement-