

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL - 600' FEL
Sec. 1, T25N, R13W, NMPM

FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF 078155

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 161

9. API Well No.

30-045-05573

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged well as follows:

1. Run tubing and tag @ 4560'.
2. Run packer - casing tested OK above 2767'.
3. Perforate Mesa Verde at 2651'.
4. Spot 77 cu. ft. Class B cement with 2% CaCl₂ @ 2665'. Displace cement to 2451'. No flow back. Mesa Verde plug 2451' - 2665'.
5. Perforate Pictured Cliffs at 1264'.
6. Spot 222 cu. ft. Class B + 4% gel cement @ 1265'. Displace cement to 822'. No flow back. Pictured Cliffs - Fruitland plug 822 - 1265'.
7. Perforate below surface casing at 275'.
8. Cement through 5 1/2" casing to bradenhead back to surface with 153 cu. ft. Class B + 4% gel cement. Left cement inside and outside casing.

Job complete 5-25-93.

Approved as to plugging of the well.
Mobility under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander

Title Operations Manager

Date 5/26/93

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

NMOCD

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side