

(SUBMIT IN TRIPLICATE)

Indian Agency \_\_\_\_\_

**Navajo Tribal**

Allottee \_\_\_\_\_

Lease No. **I-149-TND-9239**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF REDRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL <input checked="" type="checkbox"/>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**Stanolind Gulf Navajo**

**Farmington, New Mexico May 3, 1957**

Well No. **1** is located **415** ft. from **N** line and **940** ft. from **W** line of sec. **4**

**NW/4 Section 4**  
(1/4 Sec. and Sec. No.)

**T-25-N**  
(Twp.)

**R-16-W**  
(Range)

**NMPX**  
(Meridian)

**Wildest**  
(Field)

**San Juan**  
(County or Subdivision)

**New Mexico**  
(State or Territory)

The elevation of the derrick floor above sea level is **5473** ft.

**DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding, cementing points, and all other important proposed work)

**We propose to plug and abandon the above well as follows:**

- 1) Spot 115 sacks plug from 9800-10,000' in top of Mississippian-Molasse.
  - 2) Spot 60 sack plug from 8800-8900' in top of Hermosa.
  - 3) Spot 60 sacks plug from 5760-5860' in bottom of 9-5/8" pipe (GSA 5819').
  - 4) Spot 90 sack plug in 9-5/8" csg. stub (30 ft. in and 30 ft. above). (Top cement behind 9-5/8" at 4010' by temperature survey.)
  - 5) Spot 110 sack plug from 3560-3660' in top of Gallup.
  - 6) Spot 110 sack plug from 2450-2550' in top of Point Lockout.
  - 7) Spot 115 sack plug from 460-560 in bottom of 13-3/8" pipe (GSA 517').
  - 8) Spot 30 sack plug in top of surface pipe and erect surface marker.
  - 9) Restore original ground contours.
  - 10) Spot heavy mud between all plugs.
- (Verbal approval received from U. S. G. S. on 5-2-57. Long to Bower for above procedure)

Company **Pan American Petroleum Corporation**

Address **Box 487**

**Farmington, New Mexico**

By **[Signature]**

Title **Field Clerk**

