1	1
Form 9-331 Dec. 1973  USGS 1 - Brook	S Hall 1 - File Form Approved. Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEMARTMENT OF THE INTERIOR	N00-C-14-20-4151
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Navajo
SUNDRY NOTICES AND REPORTS O  (Do not use this form for proposals to drill or to deepen or plug	back to a different
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other Dry Hole	Navajo tribe
	9. WELL NO. A02
2. NAME OF OPERATOR Brooks Hall Oil Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Wildcat
101 Park Ave., Suite 600, Oklahoma City	, OK 73102 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY	Y. See space 17 AREA
below.)	Sec. 22-25N-19W
AT SURFACE: 1980' FSL & 1980' FWL AT TOP PROD. INTERVAL: NE SW AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE San Jaun NM
AT TOTAL DEPTH.	14. API NO. , .
16. CHECK APPROPRIATE BOX TO INDICATE NATUR REPORT, OR OTHER DATA	TE OF NOTICE,  15. ELEVATIONS (SHOW DF, KDB, AND WD)  GL 6008': DF, 6021'; KB 6022'
REQUEST FOR APPROVAL TO: SUBSEQUENT I	
TEST WATER SHUT-OFF	
FRACTURE TREAT  SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion and
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES U	\$EP 15.100
(other)	OIL CON 1986
	OIL CON. COM.
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIO including estimated date of starting any proposed measured and true vertical depths for all markers a</li> </ol>	work. If well is directionally drilled, give subsurface locations and
Plug and abandon well as instru	icted by U.S.G.S.
1. Spot 25 sx cement plug 4	
2. Spot 25 sx cement plug 3	425 to 3225
3. Perf 5½" Csg 1675 and squeeze w/ 50 sx cement plug; leave top cement in	
, csg at 1475	
*4. If 5½" csg not pulled squeeze bradenhead w/ 25 sx and spot 15 sx plug	
in csg from 112 to surface	
5. Install dry hole marker	1 1
	170' 00 70' across 133/2 Shoe-if Casing
not pulled, perform	te 51/2 and place in side 8 5/8" Casing

Ja Some

\*See Instructions on Reverse Side

JAMES F. SIMS
DISTRICT OIL & GAS SUPERVISOR