



UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir,
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.
SF 0780673

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Carson Unit

8. Well Name and No.
Carson Unit 21 NO.19

9. API Well No.
30-045-13273

10. Field and Pool, or Exploratory Area
Bisti Lower Gallup

11. County or Parish, State
San Juan County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Central Resources, Inc. intends to plug the well in accordance with regulations. Production equipment will be removed well will be plugged as specified. Perforate and squeeze will be used unless casing can be recovered over the specified interval or there is evidence cement is in place behind the casing.

Proposed procedure:

- Notify the Farmington BLM office at 505-599-8907 24 hours prior to commencement of plugging operations.
- Pull all retrievable downhole production equipment.
- Spot a cement plug through tubing from 4669' - 4769' to cover Gallup top @ 4769'.
- Perforate and squeeze cement from 2006' - 2106' to cover Menefee top @ 2056' inside and outside the casing.
- Perforate and squeeze cement from 1238' - 1288' to cover the Pictured Cliffs top @ 1238' inside and outside the casing.
- Perforate and squeeze cement from 804' - 904' to cover the Fruitland top @ 854' inside and outside the casing.
- Perforate and squeeze cement from 76' - 156' to cover the surface casing shoe inside and outside the production casing.
- Cut wellhead and install dry hole marker. Clear and remediate location.

Please take into account the number of existing P&A procedures, the number of P&A procedures you have requested available equipment and allow Central Resources, Inc. until the end of 2001 to complete this abandonment.

14. I hereby certify that the foregoing is true and correct

Signed Patty Shelton Title Production Tech. Date December 12, 2000

(This space for Federal or State office use)

Approved by _____ Title _____ Date 1/9/01

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side