

APPROVED

JAN 18 1956


(LONG TERM CONTRACT)

ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office **Santa Fe**  
Lease No. **NM 04226**  
Unit **Quitau**

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<b>Subsequent Report of Sandfrac</b>	<b>x</b>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 22nd, 1955

Well No. 8 is located 1204 ft. from N line and 1160 ft. from E line of sec. 11  
NE/4 NE/4 Sec. 11 25N 8W N.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Ballard PC San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7104 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

12-18-55 TD 2842'. Flowing 515 MCF/day. Sandfraced from 2792' to 2842' with 18,000 gallons salt water and 30,000\* sand, flushed with 2,800 gallons salt water. Breakdown pressure 1000\*, treating pressure 1000\*, final pressure 750\*, injection rate 38.2 barrels per minute. After 33 hours flowing 515 MCF/day.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BENSON-MONTINAddress 405 1/2 West BroadwayFarmington, New MexicoBy W. C. GreenTitle Field Superintendent