

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078474

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Z-D Presidio ~~Blk~~

9. WELL NO.

Federal No. 1

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

19 T25N R8W

12. COUNTY OR PARISH
San Juan13. STATE
N.Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐2. NAME OF OPERATOR
Zoller & Danneberg Expl. Ltd.3. ADDRESS OF OPERATOR
1600 Broadway, Denver, Colorado 802024. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface1510' FSL & 900' FWL
Sec 13 T25N R8W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6581 KB 6571 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐



SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☒(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/28/71 Spudded Drilled 200' 12 1/4 hole, set 200' 3-5/8 24" casing.
Circulated 150 sx cement to surface. Set BOP & Pressure tested
surface prior to drilling out.1/11/72 T.D. 6716 Ran & set 6715' 4-1/2 csq in 7-7/8 hole. No cores
or DSTs. Cemented 4-1/2 @ 6715 w/ 400 sx Class "A" 50/50 poz. 2% gel &
CaCl₂; @ 4594 w/ 430 sx Class "C" w/ 2% gel, w/ 50 sx Class "C" neat tail in;
@ 2090 w/ 350 sx class "C" w/ 8% gel w/ 50 sx "C" neat tail in.

1/14/72 Clean out, test casing to 4000 psi, ran cement bond log.

Perforated: 6612-24 Sand water frac w/30,000 gal slick water
6578-82 w/30,000 40/60 & 20/40 sand. Screened out.
6538-46 Subsequently tested water from each zone by
swab test with packer-plug.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE 5/1/72

(This space for Federal or State endorsement)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side