16.

UNITED STATES SUBMIT IN TRIPLICATE* (Other Instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

NM 6896 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

GEOLOGICAL	SURVEY
	

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	1/
OIL GAS WELL X OTHER	7. UNIT AUREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
El Paso Natural Gas Company	Nageezi
3. ADDRESS OF OPERATOR	9. WELL NO.
PO Box 990, Farmington, NM 87401	1 (OWWO)
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) 1500'N, 1500'E At surface	10. FIELD AND FOOL, OR WILDCAT Undes. Gallup
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OR PARISH 13. STATE 14. PERMIT NO. 6431'GL San Juan New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

• • •				• • •	
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	SUBSEQUENT REPORT OF:		
	_) , 	
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF REPAIRING WELL	
FRACTURE TREAT	<u> </u>	MULTIPLE COMPLETE		FRACTURE TREATMENT X ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING ABANDONMENT*	
REPAIR WELL		CHANGE PLANS		(Other)Plug back from Dakota to Gallup	\mathbf{x}
(Other)				(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *
- 1 22 73Stung into EZ Drill at 6461' and squeeze with 25 sks. cement. Pulled out of EZ Drill and spotted a 25 sk. cement plug. Pulled out of hole and set a Baker Model "N" Bridge Plug above cement plug at 6023'.
- PBTD 6023'. Perforated Gallup 5450-64', 5474-82', 5492-5508', 5570-78', 5600-16', 1-23-73 5642-58', with 16 shots per zone. Frac'd with 54,000# 20/40 sand, 53,030 gallons water, dropped 5 sets of 16 balls, flushed with 3700 gallons water. Set bridge plug at 5675' and tested to 4000#-OK. Perf' 5694-5702', 5734-43', 5846-54', 5898-5906', 5918-34', 5978-94' with 16 shots per zone. Frac'd with 54,000# 20/40 sand, 54, 120 gallons water, dropped 5 sets of 16 balls, flushed with 4000 gallons water.



18. I hereby certify that the foregoing is true and corre	art -	
SIGNED + COO	TITLE Petroleum Engineer	DATE March 21, 1973
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE