Form 9-331 (May 1963)

16.

UNITED STATES UNITED STATES SUBMIT IN TRIPLICATE* Other Instructions on reverse side)

Form approved. Budget Bureau No. 5. LEASE DESIGNATION AND SERIAL NO.

	NM-0468006	
SUNDR (Do not use this form Use	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
1. OIL GAS WELL X	OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME	
Tenneco Oil C	Gallegos Canyon Fed.	
3. ADDRESS OF OPERATOR		9. WELL NO.
1860 Lincoln	St., Suite 1200 Denver, Colorado 80203	1
4. LOCATION OF WELL (Repor See also space 17 below.) At surface	Basin Dakota 11. sec., T., B., M., OR BLK. AND SURVEY OR AREA	
		Sec. 3, T25N, R11W
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	6407 GR	San Juan New Mexico

TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING ABANDONMENT* REPAIR WELL CHANGE PLANS

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

6/21/75 - WIH with bit. Drilled cement stringer 3370 to 3620. Hard cement 3650 to 3727'. Pressure testing casing to 1100 psi in 10 min. Held okay.

to 5787'. Circ sand on BP and cleaned up hole.

6/22/75 - pulled bridge plug.

NOTICE OF INTENTION TO:

6/23/75 - 6/24/75 - Used csg scraper and bit. Set Model R packer @ 5781 w/seating nipple. SN above pkr. Pressure tested. Held okay. Installed X-mas tree. Swabbed hole.

6/25-6/26 Swabbing.

7/20/75 ran new Model R packer and set @ 5781. Treated down tubing w/10,000 gallons HCL in 4 stages of 2500 gallons each w/7 ball sealers between stages. AIR 8 bpm @ 3200 psi Final pressure 4200.

7/2/75 Well flowing gas and blw. Swabbed 12 hrs.

8/4/75 163 MCF. 2 bbl oil 10 bbl water.

Placed back on production.

SUBSEQUENT REPORT OF:

SEP 1 5 1975

U. S. GEOLOGICAL SURVEY FARMINGTON, N. M.

	and the state of t	
SIGNEDSIGNED	TITLE Production Clerk	DATE DEDI. 9 197
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE