UNITED STATES

SUBMIT IN TRIPLICATE*

Form approved.

	DEPARTMENT OF THE INTERIOR (Other instructions on regenerated) GEOLOGICAL SURVEY	5. LEASE DESIGNATION NOO-C-14-20-36	501	
	SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME	
	OIL GAS X OTHER	7. UNIT AGREEMENT NAT	(E	
2.	NAME OF OPERATOR	8. FARM OR LEASE NAM	E	
	TENNECO OIL COMPANY	NOCKT		
3.	ADDRESS OF OPERATOR	9. WELL NO.		
	Suite 1200 Lincoln Tower Bldg. Denver, Colo. 80203	1		
1	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* At surface	Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
	1025' FSL and 990' FEL			
		Sec. 4, T25N	J. RLIW	
14.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH		
	6433.0 GR.	San Juan	New Mexico	
16.	Charle Augustate Pau Ta Indianta Natura at Natice Pause au C	.L., D.,		

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:					SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF		PULL OR ALTER CASING			WATER SHUT-OFF	REPAIRING WELL		
FRACTURE TREAT		MULTIPLE COMPLETE			FRACTURE TREATMENT	ALTERING CASING		
SHOOT OR ACIDIZE		ABANDON*			SHOOTING OR ACIDIZING X	ABANDONMENT*		
REPAIR WELL		CHANGE PLANS			(Other)	-		
(Other)					(Note: Report results of mu Completion or Recompletion F	ltiple completion on Well teport and Log form.)		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in completion unit, installed B.O.P., Tested casing and B.O.P. to 1000 PSI. Drilled out cement and cleaned out hole to T.D. perforated 5930' - 5964' with 1 JSPF. Gas frac'd down tubing with 27,000# 20/40 sand in two stages. Maximum treating pressure 4200 PSI @ 24 BPM. Flowed to pit to clean up well. Ran 188 joints of 2-3/8", 4.6# tubing and set @ PBTD of 6045'.

Well tested 9.215 MMCFD CAOF, 20BCPD (Est.) on 3/4" choke.



8. I hereby certify that the foregoing is true and correct SIGNED W & Mave	TITLE Sr. Production Clerk	DATE Feb. 16, 1973
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE

