

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
UNIVERSAL RESOURCES CORPORATION

3. ADDRESS OF OPERATOR
1125 17TH STREET, #1800 DENVER, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650 FSL, 990 FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

JAN 21 1985

OIL CON. DIV.
DIST. 3

(NOTE: Report results of multiple completion or zone changes on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/16/83 Moved in and rigged up pulling unit.

8/17/83 Set cement retainer at 5950' and squeezed perforations with 59 CF cement. Spotted 29-1/2 CF plugs at 5124-4786', 2437-2099', 1614-1276' and 609-271'. Left 9.2#/gal brine water between plugs.

8/18/83 Made unsuccessful attempt to back casing off. Set 23.4 CF plug from 270' to 2' below ground level. Cemented 4-1/2" X 8-5/8" annulus, through 1" tubing, from 65' -2' below ground level with 13 CF cement. Installed dry hole marker and released plugging equipment.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. Millenbach TITLE Div. Oper. Eng. DATE August 31, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY:

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

Instructions on Reverse Side

NWOC.

APPROVED
AS AMENDED

DEC 12 1984

M. MILLENBACH
AREA MANAGER