5 BLM 1 File

Form 3160-5 (June 1990)

UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECOVER

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31,1993

5.	Leas	æ	Designation	and	Serial	No
٨	M	2	5443			

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reently to a different reservoir.

6. If Indian, Allotted or Tribe Name Use "APPLICATION FOR PERMIT -" for such proposals SUBMIT IN TRIPLICATE 1. Type of Well 7. If Unit or CA, Agreement Designation Othe 8. Well Name and No. 2. Name of Operator Dugan Production Corp. Red Mac #1 9. API Well No. 3. Address and Telephone No. (505) 325 - 182 30 045 21849 P.O. Box 420, Farmington, NM 87499 10. Field and Pool, or Exploratory Area Location of Well (Footage, Sec., T., R., M., or Survey Description) WAW Fruitland Sand PC 1450' FSL & 1600' FEL 11. County or Parish, State Sec. 3, T25N, R12W, NMPM San Juan, NM

12. CH	ECK APPROPRIATE BOX(s) 1	TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA				
TYPE OF SUBMISSION		TYP	TYPE OF ACTION				
X	Notice of Intent	✓ Abandonment	☐ Change of Plans				
		Recompletion	☐ New Construction				

M	Notice of Intent	1,X±1	Apandonment		ш	Change of Flans
			Recompletion			New Construction
	Subsequent Report		Plugging Back			Non-Routine Fracturing
			Casing Repair			Water Shut-Off
	Final Abandonment Notice		Altering Casing			Conversion to Injection
		X	Other	Pull & Re-cement casing		Dispose Water
		h 1				(Note: Report results of multiple completion on Well
		[Completion or Recompletion Report and Log form.)

- 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - 1. Pump cement down 2-7/8" production casing to plug Pictured Cliffs/Fruitland Coal. Top of cement inside casing will be brought to at least 1850. 700
 - 2. Pick up on 2-7/8" casing and pull in two or back off at some point in the hole. Spot cement plug wherever the casing parts or is backed off. If less than 50' of casing is recovered, the well will be plugged as previously approved.
 - 3. Remove 5-1/2" surface casing, set at 21'. It may be possible to pull this casing given its shallow setting depth. If not, wash over and pull casing.
 - 4. Drill 6-1/4" hole with mud until the top of the 2-7/8" casing is encountered.
 - 5. At this point the hole will be sidetracked and a new hole section will be drilled.
 - 6. Continue drilling with mud through Pictured Cliffs with a total depth of approximately 1250'.
 - 7. Run 4-1/2" casing and cement back to surface.
 - 8. Normal completion of Pictured Cliffs will follow.
 - 9. If drilling problems are encountered during any part of the operation, the well will be properly plugged.

4. I hereby c	ertify that the foregoing is true and correct				
Signed	John Alexander John Alexander	Vice-president	Date	9/20/2001	
	John Alexander				
This space for	Geral or State office use)				
pproved by	Title		Date	11/16/01	
andikiana af s	annual Famu				

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.