

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.6.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____				5. LEASE DESIGNATION AND SERIAL NO. N00-C-14-20-3772	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____				6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo	
2. NAME OF OPERATOR Union Oil Company of California				7. UNIT AGREEMENT NAME	
3. ADDRESS OF OPERATOR P. O. Box 2620 - Casper, WY 82601				8. FARM OR LEASE NAME Navajo (E-18)	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1500' FNL & 1150' FNL At top prod. interval reported below At total depth				9. WELL NO. 5	
15. DATE SPUDDED 5-23-76				10. FIELD AND POOL, OR WILDCAT Basin Dakota	
16. DATE T.D. REACHED 6-2-76				11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 18, T.25N., R.10W.	
17. DATE COMPL. (Ready to prod.) 6-21-76				12. COUNTY OR PARISH San Juan	
18. ELEVATIONS (DF, REB, RT, GR, ETC.)* 6482' G.L.				13. STATE New Mexico	
20. TOTAL DEPTH, MD & TVD 6315'		21. PLUG, BACK T.D., MD & TVD 6285' ETD		19. ELEV. CASINGHEAD 6482'	
22. IF MULTIPLE COMPL., HOW MANY*				23. INTERVALS DRILLED BY 0 - T.D.	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 6063-6132' (Graneros)				25. WAS DIRECTIONAL SURVEY MADE No	
26. TYPE ELECTRIC AND OTHER LOGS RUN Ran Dual Induction Log. Comp. Neutron & FDC w/Caliper				27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	785'	12-1/4"	500 Sx.	- - -
5-1/2"	15.50#	6315'	7-7/8"	850 Sx.	- - -
29. LINER RECORD					
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	
- - -	- - -	- - -	- - -	- - -	
30. TUBING RECORD					
SIZE	DEPTH SET (MD)	PACKER SET (MD)			
2-3/8"	5972.80'	5966'			
31. PERFORATION RECORD (Interval, size and number)			32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.		
6065-67') 6094-95') 6104-06') 2 Holes/Ft. 6117-28')			DEPTH INTERVAL (MD) 6065-6128' AMOUNT AND KIND OF MATERIAL USED 53,000 gals. gelled 2% KCl water w/16,000# 100-mesh sand & 96,500# 20-40 sand.		
33.* PRODUCTION					
DATE FIRST PRODUCTION 6-21-76		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing			WELL STATUS (Producing or shut-in) Shut-In
DATE OF TEST 6-21-76	HOURS TESTED 24	CHOKE SIZE 12/64"	PROD'N. FOR TEST PERIOD →	OIL—BBL. - - -	GAS—MCF. 1.68 MMCF
FLOW. TUBING PRESS. 1025#	CASING PRESSURE 0	CALCULATED 24-HOUR RATE →	OIL—BBL. - - -	GAS—MCF. 1.68 MMCFD	WATER—BBL. - - -
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) (CONTRACT PENDING)				TEST WITNESSED BY R. D. Cline	
35. LIST OF ATTACHMENTS					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records					
SIGNED R. G. Ladd, Jr.		TITLE District Drilling Supt.		DATE 7-19-76	

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

NOTE: Blowout preventers tested daily in accordance with Union Oil Company policy and reported by Drilling Contractor.

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
			No DST's.	Pictured Cliffs	1,498'	
			No Cores	Cliff House	2,368'	
				Point Lookout	4,000'	
				Mancos	4,240'	
				Gallup	5,054'	
				Greenhorn	5,932'	
				Graneros	5,998'	
				Graneros Sd.	6,091'	
				Upper Dakota	6,188'	
				Lower Dakota	6,250'	
				Morrison	6,280'	