Form	9-331
(May	196?)

Form 9-331 (May 196?)				5. LEASE DESIGNATION AND SERIAL NO. NOO-C-14-20-5195			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)					6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo		
1. OIL GAS X OTHER					7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR					8. FARM OR LEASE NA	8. FARM OR LEASE NAME	
Union Oil Company of California					Navaid K-19		
3. ADDRESS OF OPERATOR					9. WELL NO.		
P. O. Box 2620 - Casper, WY 82601					4		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)				10. FIELD AND POOL, OR WILDCAT			
At surface				Basin Dakota	Basin Dakota		
1500' FSL & 1500' FWL				11. SEC., T., R., M., OR SURVEY OR ARE	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
			•		Sec. 19, T.2	25N. R. 10W.	
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR,		ir, etc.)	12. COUNTY OR PARIS				
	6598' G.L.		L.	San Juan	New Mexico		
16.	Check A	opropriate Box To	Indicate Natur	e of Notice, Report, or (Other Data		
NOTICE OF INTENTION TO:			ł	SUBSEQUENT REPORT OF:			
TEST WATER SHU	r-off	PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING	WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING (CASING	
SHOOT OR ACIDIZE		ABANDON.*		SHOOTING OR ACIDIZING			
REPAIR WELL		CHANGE PLANS		(Other) Supplementary Well History X			
(Other)				(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
17. DESCRIBE PROPOSEI proposed work. nent to this work	OR COMPLETED OPE If well is direction.) *	RATIONS (Clearly state onally drilled, give sub	e all pertinent det osurface locations	ails, and give pertinent dates and measured and true vertice			
Spudded 12	-1/4" hole	at 3:00 p.m.,	6-4-76.				
8RD, ST&C, mixed at 1 surface.	new casing 5.8#/gallon FPDP 800#.	at 735' with Displaced Bumped plug	450 sacks with water with 1300#	and 1 piece (722 class "A" cement with full returns. Released pressure.	with 2% Calcius. Cement circure and float h	um Chloride culated to held O.K.	

to 1200# for 1/2 hour, O.K. Drilled to 2876'. Incomplete.

