

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R-1424.

5. LEASE DESIGNATION AND SERIAL NO.

NOO-C-14-20-5195

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo K-19

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 19, T.25N., R.10W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6598' G.L.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☒  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐

REPAIRING WELL

☐  
☐  
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6320' TD.

The subject well potentialized at 576 MCFD gas & 40 BOPD in June 1976. It is now producing 100% water. Attempts to repair communication and shut off water have been unsuccessful.

It is proposed to load the hole with mud, place a 50-sack cement plug in the 5-1/2" casing at 6075-5700', and bradenhead squeeze the perfs, 6028-6075'. Cement plugs will then be placed in the 5-1/2" casing at 4300-4100', 2400-2200', and 1550-1400'. The casing head will be cut off. A 25'-cement plug will be placed in the top of the casing and a dry hole marker installed. The surface will be restored as near as practical to its original condition.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. G. Ladd, Jr.

TITLE

District Drilling Supt.

DATE

1-25-78

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

JAN 30 1978

U.S. Geological Survey,  
Washington, D.C.