Form 9-331 (May 1963)

TEST WATER SHUT-OFF

FRACTURE TREAT

REPAIR WELL

(Other)

SHOOT OR ACIDIZE

OF THE INTERIOR SUBMIT IN TRIPLICATE* OF THE INTERIOR (Other instructions on reverse side) UNITED STATES

Form approved. Budget Bureau No. 42-R1424.

REPAIRING WELL

| 16. | . Check Ap | l propriate Box To | 6340' G.L. Indicate Nature of I | Notice, Report, or (| San Juan Other Data | New Mexico |
|-----|--|-----------------------|---------------------------------|--------------------------|--|------------------|
| 14. | PERMIT NO. | 15. ELEVATIONS (Sho | w whether DF, RT, GR, etc.) |) | 12. COUNTY OR PARIS | New Mexico |
| | 1500' FSL & 1150' FEL | | | | Sec. 1, T.25N.,R.11W. | |
| 4. | LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface | | | · | Basin Dakota 11. sec., T., R., M., OR BLK. AND SURVEY OR AREA | |
| - | P. O. Box 2620 - Casper, WY 82601 | | | | 3 10. FIELD AND POOL, OR WILDCAT | |
| 3. | ADDRESS OF OPERATOR | | | | 9. WELL NO. | |
| | Union Oil Company of California | | | | Navajo - | |
| | OIL GAS X OTHER NAME OF OPERATOR | -, | | | 8. FARM OR LEASE NA | AME |
| 1. | | | | | 7. UNIT AGREEMENT NAME | |
| | SUNDRY NOTION (Do not use this form for proposa Use "APPLICA" | CES AND REF | en or plug back to a dif | LLS Merent reservoir. | 6. IF INDIAN, ALLOTT | EE OR TRIBE NAME |
| | | EOLOGICAL SU | JRVEY | | NOO-C-14-20- | |

ALTERING CASING FRACTURE TREATMENT MULTIPLE COMPLETE ABANDONMENT* ABANDON*

WATER SHUT-OFF

SHOOTING OR ACIDIZING (Other) Supplementary Well History CHANGE PLANS (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded 12-1/4" hole at 2:00 p.m., 5-10-76.

PULL OR ALTER CASING

Drilled to 814'. Ran and cemented 18 joints (800.24') of 8-5/8", 24#, J-55, 8RD, ST&C, new casing at 813.24' with 550 sacks class "A" cement with 2% Calcium Chloride mixed at 14.5# to 15.8#/gal. Cement circulated to surface. C.I.P. & J.C. at 7:00 a.m., 5-11-76. W.O.C.



| | , | |
|--|-------------------------------|--------------|
| 8. I hereby certify that the foregoing is true and correct | TITLE District Drilling Supt. | DATE 5-11-76 |
| R. G. Ladd, Jr. | TITLE DISTIFICT DITTING SUPE. | DATE |
| (This space for Federal or State office use) | | |
| APPROVED BY | TITLE | DATE |