Form 9-331 (May 1963)

UNITED STATES SUBMIT IN TRIPLICATE* (Other Instructions on reverse side) Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

DATE _

| GEOLOGICAL SURVEY | NOO-C-14-20-3778 |
|---|--|
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.) | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo |
| I. OIL [□] GAS [汉] | 7. UNIT AGREEMENT NAME |
| WELL WELL A OTHER 2. NAME OF OPERATOR | 8. FARM OR LEASE NAME |
| Union Oil Company of California | Navajo I-l |
| 3. ADDRESS OF OPERATOR | 9. WELL NO. |
| P. O. Box 2620 - Casper, WY 82602 | 3 |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) | 10. FIELD AND POOL, OR WILDCAT |
| At surface | Basin Dakota 11. SEC., T., R., M., OR BLK. AND |
| 1500' FSL & 1150' FEL | Sec. 1, T25N., R11W. |
| 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, CR, etc.) | 12. COUNTY OR PARISH 13. STATE |
| 6431' G.L. | San Juan New Mexico |
| Check Appropriate Box To Indicate Nature of Notice, Report, or C | Other Data |
| •• | UENT REPORT OF: |
| | ¬ |
| TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT | REPAIRING WELL ALTERING CASING |
| SHOOTING OR ACIDIZING | ABANDONMENT* |
| SHOULD BE STATE WELL CHANGE PLANS (Other) Supplements | ary Well History X |
| (Other) (Note: Report results Completion or Recomp | s of multiple completion on Well detion Report and Log form.) |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, proposed work. If well is directionally drilled, give subsurface locations and measured and true vertice nent to this work.)* | , including estimated date of starting any al depths for all markers and zones perti- |
| 6330' OTD; 6290' ETD | |
| MIRU pulling unit. Installed BOP's. POOH with tubiduction tube and R-3 packer. Washed 6170' to 6216'. Knocked Model "B" plug out of Model "D" packer with Set packer at 6088'. Removed BOP's. Installed tree | . Tagged packer. 5000# tubing weight. |
| SITP 325#. Bled to zero in five minutes. Made 8 sv level at 1500'. Well began flowing. | wab runs with fluid |
| SITP 1200#. Bled to zero in ten minutes. Began mal for 2 hours. Recovered 20 bbls. of fluid. | king fluid. Flowed |
| SITP 1175#. Placed well back on production. Flowed water, and trace of oil. T.P. 475#. Lifting fluid rate varies from 100 MCF to 250 MCF. | d 125 MCF, 12 bbls. in heads. Flow |
| 18. I hereby certify that the foregoing is true and correct SIGNED R. G. Ladd, Jr. (This space for Federal or State office use) | upt. DATE 11-20-78 |

TITLE

APPROVED BY ________CONDITIONS OF APPROVAL, IF ANY: