



**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

SUBMIT IN TRIPPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N00-C-14-20-5248

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Canyon

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR B.L.K. AND SURVEY OR AREA

Sec. 22 - T25N - R11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR  
Tenneco Oil Company

3. ADDRESS OF OPERATOR  
1860 Lincoln St., Suite 1200, Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)  
At surface

790' FNL and 790' FEL, Unit A

14. PERMIT NO.

16. ELEVATIONS (Show whether DF, RT, GR, etc.)

6429' GL

16.

**Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data**

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL


ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Total Depth 5970'.  
Casing: 8-5/8", 24#, K-55, set at 505' and cemented to surface  
Open Hole: 7-7/8" to T.D.  
Well logged and Dakota non productive.  
Formation Tops: Dakota 5826; Grancros 5740'; Gallop - 4735'; Mancos Shale 3898';  
Mesa Verde (Cliffhouse) 2010' (Menefee) 2460' and (Point Lookout) 3718'; Chacra  
1630'; Pictured Cliffs 1252'.  
Cement plugs placed as follows on 10/11/76.  
(1) 5970' to 5750' (220') 60 sx  
(2) 4850' to 4600' (250') 75 sx  
(3) 4000' to 3800' (200') 60 sx  
(4) 2700' to 2600' (100') 35 sx  
(5) 2100' to 1900' (200') 60 sx  
(6) 1300' to 1100' (200') 60 sx  
(7) 600' to 450' (150') 50 sx  
Surface Plug 30' to surface 15 sx  
Installed dry hole marker, filled and leveled all pits, and cleaned location  
of all debris. We will reseed to your specifications when weather conditions  
are suitable.



RECEIVED  
NOV 1 1976  
U.S. GEOLOGICAL SURVEY  
SANTA FE, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*D.B. Meyer*

TITLE Div. Production Manager

DATE 10-25-76

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: