

COPIES RECEIVED	7
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	5

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
E6597-2

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
Name of Operator	8. Farm or Lease Name
Hixon Development Company	Mandana State Com
Address of Operator	9. Well No.
P. O. Box 2810, Farmington, New Mexico	1
Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER <u>C</u> , <u>790'</u> FEET FROM THE <u>North</u> LINE AND <u>1850'</u> FEET FROM	NIPP - PC
THE <u>West</u> LINE, SECTION <u>2</u> TOWNSHIP <u>25N</u> RANGE <u>12W</u> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
6272' GL	San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud date - 12-11-76 Casing set @ 32.7'(Surface)  
Total Depth - 1300'

Ran 1-joint 5 1/2" 14# 8 RD J-55 ST&C surface casing. Cemented with 8 sacks Class A cement, 2% CaCl. Drilled out from surface casing with 4 3/4" hole to a TD of 1300'. Ran 141 joints 2 7/8" 6.5# 8 RD J-55 EUE casing, with guide shoe and collar. Casing landed @ 1278.81' GL. Cemented with 75 sacks 50-50 Class B - Pozmix cement. PBD - 1270.31' GL.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. R. Kendrick TITLE Petroleum Engineer DATE December 27, 1976

Original Signed by A. R. Kendrick

APPROVED BY \_\_\_\_\_ TITLE SUPERVISOR DIST. #3 DATE DEC 28 1976

CONDITIONS OF APPROVAL, IF ANY: