Feem 9-331 (May 1963)

UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR Of the Instructions on re-

Form approved. Budget Bureau No. 42-R1424.

DLI	GEOLOGICAL SURVEY	NM-8007
	NOTICES AND REPORTS ON WELLS r proposals to drill or to deepen or plug back to a different reservoir. PPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS WELL O	THER .	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR		8. FARM OR LEASE NAME
Union Oil Com	npany of California	Federal
3. ADDRESS OF OPERATOR		9. WELL NO.
P. O. Box 26	20 - Casper, WY 82602	1 (M17)
See also space 17 below.) At surface	cation clearly and in accordance with any State requirements. SL & 1185, FWL	10. FIELD AND POOL, OR WILDCAT Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
		Sec. 17, T.25N.,R.10W.
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	6493' G.L.	San Juan New Mexico
16. Ch	eck Appropriate Box To Indicate Nature of Notice, Repor	t, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:							
		l	,				AND INC. WHILE		l
TEST WATER SHUT-OFF		PULL OR ALTER CASING			WATER SHUT-OFF		REPAIRING WELL		Į
FRACTURE TREAT		MULTIPLE COMPLETE			FRACTURE TREATMENT	_	ALTERING CASING		l
SHOOT OR ACIDIZE		ABANDON*			SHOOTING OR ACIDIZING	Ш	ABANDONMENT*		l
REPAIR WELL		CHANGE PLANS		(Other) Supplementary Well History X			X	İ	
(Other)		,			(Note: Report res Completion or Reco	ults o mplet	f multiple completion on Weltion Report and Log form.)	11	_

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Drilled to 6225' T.D.

P.O.O.H. Circulated 2 hours. Ran Compensated Neutron-Formation Density Log and Dual Induction Laterolog. R.I.H. Circulated and washed to bottom 1 hour. P.O.O.H. and laid down D.P.

Ran & cemented 5-1/2" casing at 6201' (float collar at 6173' and Howco DV tool at 4302'). Cemented 1st stage with 250 sacks cement. Dropped bomb and opened DV tool O.K. Cemented 2nd stage with 600 sacks cement. Had full returns while cementing. C.I.P. & J.C. at 7:45 p.m., 3-27-77. Released rig at 4:00 a.m., 3-28-77.



MAR 3 J 1977

18. I hereby certify that the foregoing is true and correct SIGNED	TITLE	District Drilling Supt.	DATE	3-28-77
R. G. Ladd, Jr. (This space for Federal or State office use)				
APPROVED BY	TITLE .		DATE	